

Very short Guide to install *Code_Saturne* and to run a simulation

1 – Installation

Version 4.0.6 of *Code_Saturne* Is available from `Code_Saturne-4.0.6_UEABS.tar.gz`.

The archive contains a file `Code_Saturne-4.0.6_UEABS`, which contains the installer `InstallHPC.sh` (executable) and the folder `code_saturne-4.0.6`.

The last lines of the installer (meant for the GNU compiler in this example) read:

```
$KERSRC/configure --disable-shared --disable-openmp --enable-long-gnum \
--without-modules --without-gui \
--without-libxml2 --without-hdf5 \
--without-salome-kernel --without-salome-gui \
--prefix=$KEROPT \
CC="mpicc" CFLAGS="-O3 " FC="mpif90" FCFLAGS="-O3"
```

You might have to adapt CC, FC, CFLAGS, FCFLAGS, LDFLAGS and LIBS for your machine, compilers and MPI installation.

To install the code, type

```
cd Y_PATH/Code_Saturne-4.0.6_UEABS
./InstallHPC.sh
```

When the code is installed the command **code_saturne** should return, when typing:

```
Y_PATH/Code_Saturne-4.0.6_UEABS/code_saturne-4.0.6/arch/Linux/bin/code_saturne
```

```
Y_PATH/Code_Saturne-4.0.6_UEABS/code_saturne-4.0.6/arch/Linux/bin/code_saturne <topic>
```

Topics:

- help
- autovnv
- bdiff
- bdump
- compile
- config
- create
- gui
- info
- run
- salome

Options:

-h, --help show this help message and exit

2 – Preparing the simulation

The archives `Code_Saturne_TestCaseA.tar.gz` and `Code_Saturne_TestCaseB.tar.gz` contain the information required to run both test cases, with the ***mesh_input*** file (for the mesh) and the usersubroutines in `src`.

From the working directory `WORKDIR` (pick another one than `Code_Saturne-4.0.6_UEABS`), you need to create a 'study' (TestA, for instance) and a 'case' (MACHINE, for instance) as:

```
Y_PATH/Code_Saturne-4.0.6_UEABS/code_saturne-4.0.6/arch/Linux/bin/code_saturne
create --study TestA MACHINE
```

The `TestA` directory contains 3 directories, `MACHINE`, `MESH` and `POST`.

The directory `MACHINE` contains 4 directories, `DATA`, `RESU`, `SCRIPTS` and `SRC`.

The file ***mesh_input*** should be copied into the `MESH` directory.

The user subroutines (`cs_user*` files) contained in `src` should be copied into `SRC`.

The `cs_user_scripts.py` file is used to manage the simulation. It has to be copied to `DATA` from `DATA/REFERENCE` as:

```
cd DATA
cp REFERENCE/cs_user_scripts.py .
```

At Line 138 of this file, you need to change from `None` to the global path of the mesh, i.e. `"WORKDIR/TestA/MESH/mesh_input"`

To finalise the preparation go to the folder `MACHINE` and type:

```
Y_PATH/Code_Saturne-4.0.6_UEABS/code_saturne-4.0.6/arch/Linux/bin/code_saturne
run --initialize
```

This should create a folder `RESU/YYYYMMDD-HHMM`, which should contain the following files:

```
cs_user_scripts.py
src_saturne
cs_solver
compile.log
mesh_input -> TestA/MESH/mesh_input
summary
run_solver
```

3 – Running the simulation

The name of the executable is `./cs_solver`, and you should run it with the option `--mpi` as
`mpirun/mpiexec/poe/aprun/... ./cs_solver --mpi`

References:

<http://www.code-saturne.org>

http://www.fz-juelich.de/ias/jsc/EN/Expertise/High-Q-Club/_node.html